

POLAIR

АО «Полаир-Недвижимость»
425000, Республика Марий Эл,
г. Волжск, ул. Промбаза, 1
помещение 6, этаж 1, литер-А3
www.polair.com

ПРОЕКТ:

МОДЕЛЬ:

MB109T

КОЛИЧЕСТВО:

СОГЛАСОВАНИЕ:

ДАТА:

23.10.2026



MB109T



Technical specifications

Dimensions:	1003x603x545
Temperature range, °C:	-15...- 25
Power supply system, V/Hz:	230/50
Daily power consumption, kW/h, max:	21
Refrigerant:	R290
Defrost type:	TENS
R290 refill dose, g:	150
Condenser:	Copper-aluminum
Rib pitch, mm:	2,8
Surface area, m²:	8,4
Number of fans, pcs.:	1
Fan power, W/rpm:	18/1300
Impeller diameter, mm:	254
Performance, m³/hour:	840
Air cooler:	Copper-aluminum
Rib pitch, mm:	4,2
Surface area, m²:	4,5
Number of air cooler fans, pcs.:	1

Fan power, W/rpm:	18/2600
Impeller diameter, mm:	200
Performance, m ³ /hour:	600
Air jet range, m:	4
Suction pipe diameter, mm:	10
Diameter of discharge pipe, mm:	8
80 mm room, m ³ , at ambient temperature 25°C:	2,7 ... 6
100 mm room, m ³ , at ambient temperature 25°C:	3,3 ... 7,5

The manufacturer reserves the right to make changes that do not fundamentally affect the operational properties of the equipment without prior notice.