

POLAIR

АО «Полаир-Недвижимость»
425000, Республика Марий Эл,
г. Волжск, ул. Промбаза, 1
помещение 6, этаж 1, литер-А3
www.polair.com

ПРОЕКТ:

МОДЕЛЬ:

MB109T

КОЛИЧЕСТВО:

СОГЛАСОВАНИЕ:

ДАТА:

18.06.2026



MB109T

Recommended retail price: 150 236 rub



Technical specifications

| | |
|-------------------------------------|-----------------|
| Dimensions: | 1003x603x545 |
| Temperature range, °C: | -15...- 25 |
| Power supply system, V/Hz: | 230/50 |
| Daily power consumption, kW/h, max: | 21 |
| Refrigerant: | R290 |
| Defrost type: | TENS |
| R290 refill dose, g: | 150 |
| Condenser: | Copper-aluminum |
| Rib pitch, mm: | 2,8 |
| Surface area, m²: | 8,4 |
| Number of fans, pcs.: | 1 |
| Fan power, W/rpm: | 18/1300 |
| Impeller diameter, mm: | 254 |
| Performance, m³/hour: | 840 |
| Air cooler: | Copper-aluminum |
| Rib pitch, mm: | 4,2 |

| | |
|--|-------------|
| Surface area, m ² : | 4,5 |
| Number of air cooler fans, pcs.: | 1 |
| Fan power, W/rpm: | 18/2600 |
| Impeller diameter, mm: | 200 |
| Performance, m ³ /hour: | 600 |
| Air jet range, m: | 4 |
| Suction pipe diameter, mm: | 10 |
| Diameter of discharge pipe, mm: | 8 |
| 80 mm room, m ³ , at ambient temperature 25°C: | 2,7 ... 6 |
| 100 mm room, m ³ , at ambient temperature 25°C: | 3,3 ... 7,5 |

The manufacturer reserves the right to make changes that do not fundamentally affect the operational properties of the equipment without prior notice.