



SM342S

Recommended retail price: 242 985 rub



Technical specifications

Temperature range, °C:	-5...+10
Power supply system, V/Hz:	380/50
Power consumption, W, max.:	3100
Daily power consumption, kW/h, max:	45
Refrigerant:	R404A
Defrost type:	electric
R404 refill dose, g:	1500
Condenser:	Copper-aluminum
Rib pitch, mm:	3,2
Surface area, m ² :	19,5
Number of fans, pcs.:	1
Fan power, W/rpm:	105/1350
Impeller diameter, mm:	315
Performance, m ³ /hour:	1850
Air cooler:	Copper-aluminum
Rib pitch, mm:	3,6

Surface area, m ² :	15
Number of air cooler fans, pcs.:	1
Fan power, W/rpm:	105/1350
Impeller diameter, mm:	315
Air jet range, m:	9
Suction pipe diameter, mm:	18
Diameter of discharge pipe, mm:	10
External power cable:	4x1.5+1x1.5
Power connector/cable:	4x1+1x1,0
Sensor connection:	3x0,75
Performance, m ³ /hour:	1850
External unit dimensions, mm:	790x417x704
Dimensions of the indoor unit, mm:	800x480x500
Room m ³ , at ambient temperature 25°C:	37 ... 62

The manufacturer reserves the right to make changes that do not fundamentally affect the operational properties of the equipment without prior notice.