

POLAIR

АО «Полаир-Недвижимость»
425000, Республика Марий Эл,
г. Волжск, ул. Промбаза, 1
помещение 6, этаж 1, литер-А3
www.polair.com

ПРОЕКТ:

МОДЕЛЬ:

SB216S

КОЛИЧЕСТВО:

СОГЛАСОВАНИЕ:

ДАТА:

30.04.2026



SB216S

Recommended retail price: 183 600 rub



Technical specifications

Temperature range, °C:	-15...- 25
Power supply system, V/Hz:	380/50
Power consumption, W, max.:	2100
Daily power consumption, kW/h, max:	30
Refrigerant:	R404A
Defrost type:	electric
R404 refill dose, g:	900
Condenser:	Copper-aluminum
Rib pitch, mm:	3,2
Surface area, m ² :	11,14
Number of fans, pcs.:	2
Fan power, W/rpm:	18/1300
Impeller diameter, mm:	254
Performance, m ³ /hour:	1200
Air cooler:	Copper-aluminum
Rib pitch, mm:	3,6

Surface area, m ² :	8,93
Number of air cooler fans, pcs.:	2
Fan power, W/rpm:	18/2600
Impeller diameter, mm:	200
Air jet range, m:	4
Suction pipe diameter, mm:	16
Diameter of discharge pipe, mm:	8
External power cable:	4x1.5+1x1.5
Power connector/cable:	4x1+1x1,0
Sensor connection:	3x0,75
Performance, m ³ /hour:	1200
External unit dimensions, mm:	790x315x704
Dimensions of the indoor unit, mm:	715x420x284
80 mm room, m ³ , at ambient temperature 25°C:	7,1 ... 15,2
100 mm room, m ³ , at ambient temperature 25°C:	8 ... 19

The manufacturer reserves the right to make changes that do not fundamentally affect the operational properties of the equipment without prior notice.